



## System concept

The high-class charging station for the Vectron POS MobilePro III lends itself to secure storage of the POS system while at the same time the battery can be charged in the POS system. During the charging you can operate the Vectron POS MobilePro III in the charging station.



## Hardware

Technical data of the Vectron POS MobilePro III charging station	
<b>Input voltage</b>	permissible supply voltage 12 - 24V
<b>Power consumption</b>	8 W in normal operation; 0.5 W in standby
<b>Temperature</b>	operation: 0° - 40°C (the battery in the POS system can only be loaded as of 5°C for safety reasons)
<b>Dimensions (W x H x D)</b>	103.7 x 93.4 x 121.4 mm
<b>Weight</b>	ca. 400 g
<b>Certified</b>	CE

Technical data of power supply Vectron PS80	
<b>Input voltage</b>	100 to 240 V alternating voltage
<b>Output voltage</b>	+ 24 V direct voltage
<b>Output current</b>	max. 1.67 A
<b>Output power</b>	maximal 40 W
<b>Power consumption</b>	max. 44 W
<b>No-load loss</b>	max. 0.3 W
<b>Temperature</b>	storage: -40 to 85 °C operation: -30 to 60 °C
<b>Air humidity</b>	90 %, non condensing
<b>Dimensions (W x H x D)</b>	125 x 50 x 32.5 mm
<b>Weight</b>	280 g
<b>Certified</b>	CE, UL



# Shipment

Vectron POS Mobile Pro III charging station	
<b>Standard shipment</b>	charging station for one POS system dispatch box
<b>Optional accessories</b>	external power supply PS80 (you can order the charging station without power supply; to operate the charging station, however, the power supply is required)

## Dimensions (in mm and inch)

